

# Eaton 286467

Catalog Number: 286467

Eaton Moeller series xPole - PFL6/7 RCBO - residual-current circuit breaker with overcurrent protection. RCD/MCB, 16A, 30mA, MCB trip curve C, 1pole+N, RCCB trip type: AC, PFL6



Fotografia este reprezentativa

## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Moeller series xPole - PFL6/7 RCBO - residual-current circuit breaker with overcurrent protection	286467 EAN 4015082864675
<b>Product Length/Depth</b>	<b>Product Height</b>
86 mm	75 mm
<b>Product Width</b>	<b>Product Weight</b>
37 mm	0.225 kg
<b>Compliances</b>	<b>Certifications</b>
CE Marked RoHS conform	CE
	<b>Model Code</b> PFL6-16/1N/C/003

## Delivery program

### Application

Switchgear for residential and commercial applications

### Product range

PFL6

### Basic function

Combined RCD/MCB devices

### Number of poles

Single-pole + N

### Number of poles (protected)

1

### Number of poles (total)

2

### Tripping characteristic

C

### Release characteristic

C

### Amperage Rating

16 A

### Rated current

16 A

### Fault current rating

0.03 A

### Sensitivity type

Type AC, AC current sensitive.

### Type

RCBO

## Technical data - electrical

### Voltage type

AC

### Voltage rating

230 V

### Rated operational voltage (U<sub>e</sub>) - max

230 V

### Rated insulation voltage (U<sub>i</sub>)

440 V

### Rated impulse withstand voltage (U<sub>imp</sub>)

4 kV

### Impulse withstand current

Partly surge-proof, 250 A

### Frequency rating

50 Hz

### Leakage current type

AC

### Rated switching capacity

6 kA

### Rated switching capacity (IEC/EN 61009)

6 kA

### Rated short-circuit breaking capacity (EN 60947-2)

0 kA

### Rated short-circuit breaking capacity (EN 61009)

6 kA

### Rated short-circuit breaking capacity (EN 61009-1)

6 kA

### Rated short-circuit breaking capacity (IEC 60947-2)

0 kA

### Surge current capacity

0.25 kA

### Disconnection characteristic

Undelayed

### Tripping

Non-delayed

### Overvoltage category

III

Pollution degree

2

## Technical data - mechanical

Width in number of modular spacings

2

Built-in depth

69.5 mm

Degree of protection

IP20

Connectable conductor cross section (solid-core) - min

1 mm<sup>2</sup>

Connectable conductor cross section (solid-core) - max

25 mm<sup>2</sup>

Connectable conductor cross section (multi-wired) - min

1 mm<sup>2</sup>

Connectable conductor cross section (multi-wired) - max

25 mm<sup>2</sup>

## Design verification as per IEC/EN 61439 - technical data

Rated operational current for specified heat dissipation (In)

16 A

Heat dissipation per pole, current-dependent

0 W

Equipment heat dissipation, current-dependent

3.2 W

Static heat dissipation, non-current-dependent

0 W

Heat dissipation capacity

0 W

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

40 °C

## Design verification as per IEC/EN 61439

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

### 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

### 10.4 Clearances and creepage distances

Meets the product standard's requirements.

### 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

### 10.8 Connections for external conductors

Is the panel builder's responsibility.

#### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

#### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

#### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Additional information

### Current limiting class

3

### Features

Concurrently switching N-neutral

## Resurse

### Cataloage

[eaton-xpole-pf17-rcbo-catalog-ca019045en-en-us.pdf](#)

[eaton-xpole-pf16-rcbo-catalog-ca019046en-en-us.pdf](#)

### Characteristic curve

[eaton-xpole-pf16-7-characteristic-curve-002.jpg](#)

### Desene

[eaton-xeffect-frbm6m-wiring-diagram.jpg](#)

[eaton-xpole-pkn6-m-dimensions.jpg](#)

[eaton-xpole-pkn6-m-3d-drawing.jpg](#)

### Rapoarte de certificare

[DA-DC-03\\_PFL](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton Toate  
drepturile rezervate.

Eaton is a registered trademark.

All other trademarks are  
property of their respective  
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)