

# Eaton 286598

Catalog Number: 286598

Eaton Moeller series xPole - PL6 MCB. PL6, 3-pole, tripping characteristic: C, rated current  $I_n$ : 6 A, rated switching capacity IEC/EN 60898-1: 6 kA



## General specifications

Product Name	Catalog Number
Eaton Moeller series xPole - PL6 MCB	286598
EAN	Product Length/Depth
4015082865986	85 mm
Product Height	Product Width
73 mm	53.1 mm
Product Weight	Compliances
0.36 kg	RoHS conform
Model Code	
PL6-C6/3	

## Delivery program

### Application

Switchgear for residential and commercial applications  
xPole - Switchgear for residential and commercial applications

### Number of poles

Three-pole

### Number of poles (total)

3

### Number of poles (protected)

3

### Tripping characteristic

C

### Release characteristic

C

### Amperage Rating

6 A

### Type

Miniature circuit breaker  
PL6

## Technical data - electrical

### Voltage type

AC

### Rated operational voltage (U<sub>e</sub>) - max

400 V

### Rated insulation voltage (U<sub>i</sub>)

440 V

### Rated impulse withstand voltage (U<sub>imp</sub>)

4 kV

### Frequency rating - min

50 Hz

### Frequency rating - max

60 Hz

### Rated switching capacity (IEC/EN 60898-1)

6 kA

### Rated short-circuit breaking capacity (EN 60898) at 230 V

6 kA

### Rated short-circuit breaking capacity (EN 60898) at 400 V

6 kA

### Rated short-circuit breaking capacity (IEC 60947-2) at 230 V

0 kA

### Rated short-circuit breaking capacity (IEC 60947-2) at 400 V

0 kA

### Overvoltage category

III

### Pollution degree

2

## Technical data - mechanical

### Width in number of modular spacings

3

### Built-in depth

70.5 mm

### Degree of protection

IP20

## Design verification as per IEC/EN 61439 - technical data

### Rated operational current for specified heat dissipation (I<sub>n</sub>)

6 A

### Heat dissipation per pole, current-dependent

0 W

### Equipment heat dissipation, current-dependent

4.4 W

Connectable conductor cross section (solid-core) - min

1 mm<sup>2</sup>

Connectable conductor cross section (solid-core) - max

25 mm<sup>2</sup>

Connectable conductor cross section (multi-wired) - min

1 mm<sup>2</sup>

Connectable conductor cross section (multi-wired) - max

25 mm<sup>2</sup>

Static heat dissipation, non-current-dependent

0 W

Heat dissipation capacity

0 W

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

75 °C

## Design verification as per IEC/EN 61439

### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

#### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

#### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

#### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

### 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

### 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

### 10.2.7 Inscriptions

Meets the product standard's requirements.

## 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

## 10.4 Clearances and creepage distances

Meets the product standard's requirements.

## 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

## Resurse

### Cataloge

[eaton-miniature-circuit-breaker-xpole-pl6-catalog-ca20190212-en-us.pdf](#)

[eaton-xpole-pl6-mcb-catalog-ca019069en-en-us.pdf](#)

### Characteristic curve

[eaton-xpole-mm4-6-m-mcb-characteristic-curve-002.jpg](#)

### Desene

[eaton-xpole-pl6-mcb-dimensions.jpg](#)

[eaton-xpole-pl6-mcb-3d-drawing-002.jpg](#)

### Rapoarte de certificare

[DA-DC-03\\_PL6](#)

### Scheme electrice

[eaton-xpole-mm4-6-m-mcb-wiring-diagram-005.jpg](#)

#### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

#### 10.8 Connections for external conductors

Is the panel builder's responsibility.

#### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

#### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

#### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

#### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

#### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.