

Eaton 277950

Catalog Number: 277950

Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 2 N/O, 2 NC, Front fixing, Screw terminals, DILM40 - DILM170

General specifications



Product Name	Catalog Number
Eaton Moeller® series DILM auxiliary contact module	277950
	EAN
	4015082779504
Product Length/Depth	Product Height
39 mm	46 mm
Product Width	Product Weight
45 mm	0.055 kg
Certifications	Model Code
IEC/EN 60947	DILM150-XHI22
UL	
CSA Class No.: 3211-03	
CSA File No.: 012528	
UL File No.: E29184	
CSA	
UL 508	
CE	
IEC/EN 60947-4-1	
VDE 0660	
CSA-C22.2 No. 14-05	
UL Category Control No.: NKCR	

Features Functions

Features

Interlocked opposing contacts within an auxiliary contact module (according to IEC 60947-5-1 Annex L)

Functions

For standard applications

Fitted with:

Interlocked opposing contacts

Number of poles

Four-pole

Electric connection type

Screw connection

General

Degree of protection

IP20

Lifespan, electrical

1,300,000 Operations (at 230 V, AC-15, 3 A)

Model

Top mounting

Mounting method

Front fastening

Overvoltage category

III

Pollution degree

3

Protection

Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

Rated impulse withstand voltage (Uimp)

6000 V AC

Type

Front mounting auxiliary contact

Ambient conditions, mechanical

Shock resistance

5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

Climatic environmental conditions

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

60 °C

Ambient operating temperature (enclosed) - min

-25 °C

Ambient operating temperature (enclosed) - max

40 °C

Ambient storage temperature - min

-40 °C

Ambient storage temperature - max

80 °C

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Electrical rating

Rated operational current (I_e)

6 A at 60 V, DC L/R ≤ 15 ms (with 1 contact in series)

1 A at 220 V, DC L/R ≤ 15 ms (with 1 contact in series)

10 A at 24 V, DC L/R ≤ 15 ms (with 1 contact in series)

3 A at 110 V, DC L/R ≤ 15 ms (with 1 contact in series)

Rated operational current (I_e) at AC-15, 220 V, 230 V, 240 V
6 A

Rated operational current (I_e) at AC-15, 380 V, 400 V, 415 V
4 A

Rated operational current (I_e) at AC-15, 500 V
1.5 A

Rated insulation voltage (U_i)
690 V

Rated operational voltage (U_e) at AC - max
500 V

Terminal capacities

Terminal capacity (flexible with ferrule)

2 x (0.75 - 2.5) mm²

1 x (0.75 - 2.5) mm²

Terminal capacity (solid)

2 x (0.75 - 2.5) mm²

1 x (0.75 - 2.5) mm²

Terminal capacity (solid/stranded AWG)

18 - 14

Screwdriver size

0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver
2, Terminal screw, Pozidriv screwdriver

Tightening torque

1.2 Nm, Screw terminals

Short-circuit rating

Short-circuit protection rating

Max. 16 A gG/gL, Fuse, Without welding, Auxiliary contacts

Short-circuit protection rating without welding

16 A gG/gL, 500 V, Max. Fuse, Contacts

Conventional thermal current I_{th}

Conventional thermal current I_{th} at 60°C (3-pole, open)

16 A

Switching capacity

Switching capacity (auxiliary contacts, general use)

15 A, 600 V AC, (UL/CSA)

1 A, 250 V DC, (UL/CSA)

Switching capacity (auxiliary contacts, pilot duty)

P300, DC operated (UL/CSA)

A600, AC operated (UL/CSA)

Communication

Connection

Screw terminals

Contacts

Control circuit reliability

$\lambda < 5 \times 1/10^7$ (1 failure at 2,000,000 operations for $U_e = 24$ V DC, $U_{min} = 17$ V, $I_{min} = 5.4$ mA)

Number of contacts (change-over contacts)

0

Number of contacts (normally closed contacts)

2

Number of contacts (normally open contacts)

2

Safety

Safe isolation

440 V AC, Between auxiliary contacts, According to EN 61140

440 V AC, Between coil and auxiliary contacts, According to EN 61140

Design verification

Equipment heat dissipation, current-dependent P_{vid}

0 W

Heat dissipation capacity P_{diss}

0 W

Heat dissipation per pole, current-dependent P_{vid}

0.23 W

Rated operational current for specified heat dissipation (I_n)

4 A

Static heat dissipation, non-current-dependent P_{vs}

0 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resurse

Desene

[eaton-contactors-contact-dilm-accessory-3d-drawing-004.eps](#)

Instrucțiuni de instalare

[IL03407034Z](#)

mCAD model

[dil_m150_xhi_4.stp](#)

Rapoarte de certificare

[DA-DC-00004070.pdf](#)

[DA-DC-00004229.pdf](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton Toate
drepturile rezervate.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)