

Eaton 277834

Catalog Number: 277834

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 22 kW, 24 V 50/60 Hz, AC operation, Screw terminals



Fotografia este reprezentativa

General specifications

Product Name	Catalog Number
Eaton Moeller® series DILM contactor	277834
EAN	Product Length/Depth
4015082778347	132.1 mm
Product Height	Product Width
115 mm	55 mm
Product Weight	Certifications
0.872 kg	IEC/EN 60947
	CSA
	VDE 0660
	CE
	UL 60947-4-1
	UL
	UL File No.: E29096
	CSA Class No.: 2411-03, 3211-04
	IEC/EN 60947-4-1
	UL Category Control No.: NLDX
	CSA File No.: 012528
	CSA-C22.2 No. 60947-4-1-14
Catalog Notes	Model Code
Contacts according to EN 50012	DILM50(24V50/60HZ)

Features Functions

Number Of Poles

Three-pole

General

Application

Contactors for Motors

Degree of protection

IP00

Frame size

FS3

Lifespan, mechanical

10,000,000 Operations (AC operated)

7,000,000 Operations (Coil 50/60 Hz)

Operating frequency

5000 mechanical Operations/h (AC operated)

Overvoltage category

III

Pollution degree

3

Product category

Contactors

Protection

Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

Rated impulse withstand voltage (Uimp)

8000 V AC

Resistance per pole

1.9 m Ω

Suitable for

Also motors with efficiency class IE3

Utilization category

AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-4: Normal AC induction motors: starting, plugging, reversing, inching

AC-3: Normal AC induction motors: starting, switch off during running

Voltage type

AC

Ambient conditions, mechanical

Shock resistance

7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms

5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms

10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms

5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

Climatic environmental conditions

Altitude

Max. 2000 m

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

60 °C

Ambient operating temperature (enclosed) - min

25 °C

Ambient operating temperature (enclosed) - max

40 °C

Ambient storage temperature - min

40 °C

Ambient storage temperature - max

80 °C

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

Electro magnetic compatibility

Emitted interference

According to EN 60947-1

Interference immunity

According to EN 60947-1

Terminal capacities

Terminal capacity (copper band)

2 x (6 x 9 x 0.8) mm (Number of segments x width x thickness),
Main cables

Terminal capacity (flexible with ferrule)

2 x (0.75 - 2.5) mm², Control circuit cables
1 x (0.75 - 35) mm², Main cables
2 x (0.75 - 25) mm², Main cables
1 x (0.75 - 2.5) mm², Control circuit cables

Terminal capacity (solid)

2 x (0.75 - 16) mm², Main cables
1 x (0.75 - 4) mm², Control circuit cables
2 x (0.75 - 2.5) mm², Control circuit cables
1 x (0.75 - 16) mm², Main cables

Terminal capacity (solid/stranded AWG)

Single 14 - 1, double 14 - 2, Main cables
18 - 14, Control circuit cables

Terminal capacity (stranded)

1 x (16 - 50) mm², Main cables

2 x (16 - 35) mm², Main cables

Stripping length (main cable)

14 mm

Stripping length (control circuit cable)

10 mm

Screw size

M6, Terminal screw, Main cables

M3.5, Terminal screw, Control circuit cables

Screwdriver size

2, Terminal screw, Pozidriv screwdriver

0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver

Tightening torque

3.3 Nm, Screw terminals, Main cables

1.2 Nm, Screw terminals, Control circuit cables

Electrical rating

Rated breaking capacity at 220/230 V

500 A

Rated breaking capacity at 380/400 V

500 A

Rated breaking capacity at 500 V

500 A

Rated breaking capacity at 660/690 V

320 A

Rated operational current (I_e) at AC-1, 380 V, 400 V, 415 V

80 A

Rated operational current (I_e) at AC-3, 220 V, 230 V, 240 V

50 A

Rated operational current (I_e) at AC-3, 380 V, 400 V, 415 V

50 A

Rated operational current (I_e) at AC-3, 440 V

50 A

Rated operational current (I_e) at AC-3, 500 V

50 A

Rated operational current (I_e) at AC-3, 660 V, 690 V

32 A

Rated operational current (I_e) at AC-4, 220 V, 230 V, 240 V

21 A

Rated operational current (I_e) at AC-4, 440 V

21 A

Rated operational current (I_e) at AC-4, 500 V

21 A

Rated operational current (I_e) at AC-4, 660 V, 690 V

17 A

Rated operational current (I_e) at DC-1, 60 V

60 A

Rated operational current (I_e) at DC-1, 110 V

50 A

Rated operational current (I_e) at DC-1, 220 V

45 A

Rated insulation voltage (U_i)

690 V

Rated making capacity up to 690 V (cos phi to IEC/EN 60947)

700 A

Rated operational power at AC-3, 240 V, 50 Hz

17 kW

Rated operational power at AC-3, 380/400 V, 50 Hz

22 kW

Rated operational power at AC-3, 415 V, 50 Hz

30 kW

Rated operational power at AC-3, 440 V, 50 Hz

32 kW

Rated operational power at AC-3, 500 V, 50 Hz

36 kW

Rated operational power at AC-3, 690 V, 50 Hz

30 kW

Rated operational power at AC-4, 220/230 V, 50 Hz

6 kW

Rated operational power at AC-4, 240 V, 50 Hz

6.5 kW

Rated operational power at AC-4, 415 V, 50 Hz

11 kW

Rated operational power at AC-4, 440 V, 50 Hz

12 kW

Rated operational power at AC-4, 500 V, 50 Hz

13 kW

Rated operational power at AC-4, 660/690 V, 50 Hz

14 kW

Rated operational voltage (Ue) at AC - max

690 V

Switching capacity

Switching capacity (main contacts, general use)

80 A, Maximum motor rating (UL/CSA)

Short-circuit rating

Short-circuit current rating (basic rating)

250 A, max. CB, SCCR (UL/CSA)

250 A, max. Fuse, SCCR (UL/CSA)

10 kA, SCCR (UL/CSA)

Short-circuit current rating (high fault at 480 V)

30/100 kA, Fuse, SCCR (UL/CSA)

100 A, max. CB, SCCR (UL/CSA)

250/150 A, Class J, max. Fuse, SCCR (UL/CSA)

65 kA, CB, SCCR (UL/CSA)

Short-circuit current rating (high fault at 600 V)

30 kA, CB, SCCR (UL/CSA)

250 A, max. CB, SCCR (UL/CSA)

30/100 kA, Fuse, SCCR (UL/CSA)

250/150 A, Class J, max. Fuse, SCCR (UL/CSA)

Short-circuit protection rating (type 1 coordination) at 400 V

160 A gG/gL

Short-circuit protection rating (type 1 coordination) at 690 V

80 A gG/gL

Short-circuit protection rating (type 2 coordination) at 400 V

80 A gG/gL

Short-circuit protection rating (type 2 coordination) at 690 V

63 A gG/gL

Conventional thermal current I_{th}

Conventional thermal current I_{th} (1-pole, enclosed)

145 A

Conventional thermal current I_{th} (3-pole, enclosed)

58 A

Conventional thermal current I_{th} at 55°C (3-pole, open)

68 A

Conventional thermal current I_{th} of main contacts (1-pole, open)

162 A

Magnet system

Arcing time

10 ms

Drop-out voltage

AC operated: 0.6 - 0.3 x UC, AC operated

Duty factor

100 %

Pick-up voltage

0.8 - 1.1 V AC x Uc

Power consumption, pick-up, 50 Hz

154 VA, Dual-frequency coil in a cold state and 1.0 x Us

168 VA, Dual-frequency coil in a cold state and 1.0 x Us

Power consumption, pick-up, 60 Hz

154 VA, Dual-frequency coil in a cold state and 1.0 x Us

168 VA, Dual-frequency coil in a cold state and 1.0 x Us

Power consumption, sealing, 50 Hz

4.1 W, Dual-frequency coil in a cold state and 1.0 x Us

Power consumption, sealing, 60 Hz

14 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz

22 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz

4.1 W, Dual-frequency coil in a cold state and 1.0 x Us

Rated control supply voltage (Us) at AC, 50 Hz - min

24 V

Rated control supply voltage (Us) at AC, 50 Hz - max

24 V

Rated control supply voltage (Us) at AC, 60 Hz - min

24 V

Rated control supply voltage (Us) at AC, 60 Hz - max

24 V

Rated control supply voltage (Us) at DC - min

0 V

Rated control supply voltage (Us) at DC - max

0 V

Switching time (AC operated, make contacts, closing delay) - min

12 ms

Switching time (AC operated, make contacts, closing delay) - max

18 ms

Switching time (AC operated, make contacts, opening delay) - min

8 ms

Switching time (AC operated, make contacts, opening delay) -

Motor rating

Assigned motor power at 115/120 V, 60 Hz, 1-phase

3 HP

Assigned motor power at 200/208 V, 60 Hz, 3-phase

15 HP

Assigned motor power at 230/240 V, 60 Hz, 1-phase

10 HP

Assigned motor power at 230/240 V, 60 Hz, 3-phase

20 HP

Assigned motor power at 460/480 V, 60 Hz, 3-phase

40 HP

Assigned motor power at 575/600 V, 60 Hz, 3-phase

50 HP

Communication

Connection

Screw terminals

Connection to SmartWire-DT

No

Contacts

Number of auxiliary contacts (normally closed contacts)

0

Number of auxiliary contacts (normally open contacts)

0

Safety

Safe isolation

440 V AC, Between coil and contacts, According to EN 61140

440 V AC, Between the contacts, According to EN 61140

Special purpose ratings

Special purpose rating of ballast electrical discharge lamps

79 A (600V 60Hz 3phase, 347V 60Hz 1phase)

max

13 ms

79 A (480V 60Hz 3phase, 277V 60Hz 1phase)

Special purpose rating of elevator control

40 A, 480 V 60 Hz 3-ph, (UL/CSA)

10 HP, 200 V 60 Hz 3-ph, (UL/CSA)

30 HP, 480 V 60 Hz 3-ph, (UL/CSA)

15 HP, 240 V 60 Hz 3-ph, (UL/CSA)

32.2 A, 200 V 60 Hz 3-ph, (UL/CSA)

42 A, 240 V 60 Hz 3-ph, (UL/CSA)

40 HP, 600 V 60 Hz 3-ph, (UL/CSA)

41 A, 600 V 60 Hz 3-ph, (UL/CSA)

Special purpose rating of resistance air heating

79 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA)

79 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA)

Special purpose rating of tungsten incandescent lamps

74 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA)

74 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA)

Design verification

Equipment heat dissipation, current-dependent P_{vid}

9.9 W

Heat dissipation capacity P_{diss}

0 W

Heat dissipation per pole, current-dependent P_{vid}

3.3 W

Rated operational current for specified heat dissipation (I_n)

50 A

Static heat dissipation, non-current-dependent P_{vs}

4.1 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

Resurse

Characteristic curve

[eaton-contactors-switch-dilm-characteristic-curve.eps](#)

[eaton-contactors-switch-dilm-characteristic-curve-002.eps](#)

Desene

[eaton-contactors-dilm-dimensions-002.eps](#)

Instrucțiuni de instalare

[IL03407033Z](#)

mCAD model

[dil_m40_65_22.stp](#)

[dil_m40_65_22.dwg](#)

Rapoarte de certificare

[DA-DC-00004070.pdf](#)

[DA-DC-00004229.pdf](#)

Scheme electrice

[eaton-contactors-contact-dilm-wiring-diagram-003.eps](#)

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton Toate
drepturile rezervate.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)