

Eaton 189892

Catalog Number: 189892

Eaton Moeller® series PKZM01 Motor-protective circuit-breaker, 660 V 690 V: 15 kW, I_r= 16 - 20 A, IP20 PKZM01-20-EA



Fotografia este reprezentativa

General specifications

Product Name	Catalog Number
Eaton Moeller® series PKZM01 Motor-protective circuit-breaker	189892
	EAN
	4015081878888
Product Length/Depth	Product Height
93 mm	90 mm
Product Width	Product Weight
45 mm	0.299 kg
Compliances	Model Code
CE Marked	PKZM01-20-EA
RoHS conform	

Caracteristici & funcții

Actuator type

Push button

Functions

Phase failure sensitive

Number of poles

Three-pole

Tensiune nominală

Rated operational power at AC-3, 220/230 V, 50 Hz
5.5 kW

Rated operational power at AC-3, 380/400 V, 50 Hz
9 kW

Rated operational voltage (Ue) - min
440 V

Rated operational voltage (Ue) - max
440 V

Rated uninterrupted current (Iu)
20 A

Grad de protecție la scurtcircuit

Short-circuit current rating (group protection)

10 kA, 600 V High Fault, Fuse, SCCR (UL/CSA) with 150 A, 600 V High Fault, Fuse, SCCR (UL/CSA)

10 kA, 600 V High Fault, CB, SCCR (UL/CSA) with 125 A, 600 V High Fault, CB, SCCR (UL/CSA)

18 kA, 600 V High Fault, Fuse with CL, SCCR (UL/CSA) with 600 A, 600 V High Fault, Fuse with CL, SCCR (UL/CSA)

18 kA, 600 V High Fault, CB with CL, SCCR (UL/CSA) with 600 A, 600 V High Fault, CB with CL, SCCR (UL/CSA)

18 kA, 480 V High Fault, CB, SCCR (UL/CSA) with 600 A, 480 V High Fault, CB, SCCR (UL/CSA)

18 kA, 480 V High Fault, Fuse, SCCR (UL/CSA) with 600 A, 480 V High Fault, Fuse, SCCR (UL/CSA)

Bloc de declanșare

Overload release current setting - min
16 A

Overload release current setting - max
20 A

Resurse

Characteristic curve

[eaton-manual-motor-starters-pkz-characteristic-curve-003.eps](#)

[eaton-manual-motor-starters-characteristic-characteristic-curve-008.eps](#)

Instrucțiuni de instalare

IL034045ZU