

# Eaton 277004

Catalog Number: 277004

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 7.5 kW, 1 N/O, 230 V 50 Hz, 240 V 60 Hz, AC operation, Screw terminals DILM17-10(230V50HZ,240V60HZ)



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Moeller® series DILM contactor	277004
<b>EAN</b>	<b>Product Length/Depth</b>
4015082770044	97 mm
<b>Product Height</b>	<b>Product Width</b>
85 mm	45 mm
<b>Product Weight</b>	<b>Certifications</b>
0.428 kg	CSA Class No.: 2411-03, 3211-04 CSA File No.: 012528 CE IEC/EN 60947-4-1 UL Category Control No.: NLDX CSA-C22.2 No. 60947-4-1-14 UL 60947-4-1 CSA VDE 0660 UL IEC/EN 60947 UL File No.: E29096
<b>Catalog Notes</b>	<b>Model Code</b>
Contacts according to EN 50012	DILM17-10(230V50HZ,240V60HZ)

## Features Functions

### Number Of Poles

Three-pole

## General

### Application

Contactors for Motors

### Degree of protection

IP00

### Frame size

FS2

### Lifespan, mechanical

10,000,000 Operations (AC operated)

### Operating frequency

5000 mechanical Operations/h (AC operated)

### Overvoltage category

III

### Pollution degree

3

### Product category

Contactors

### Protection

Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

### Rated impulse withstand voltage (Uimp)

8000 V AC

### Resistance per pole

2.7 mΩ

### Suitable for

Also motors with efficiency class IE3

### Utilization category

AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-4: Normal AC induction motors: starting, plugging, reversing, inching

AC-3: Normal AC induction motors: starting, switch off during running

### Voltage type

AC

## Ambient conditions, mechanical

## Climatic environmental conditions

### Shock resistance

7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms  
6.9 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms  
10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms  
5.3 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms  
5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms  
3.5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms

### Altitude

Max. 2000 m

### Ambient operating temperature - min

-25 °C

### Ambient operating temperature - max

60 °C

### Ambient operating temperature (enclosed) - min

-25 °C

### Ambient operating temperature (enclosed) - max

40 °C

### Ambient storage temperature - min

-40 °C

### Ambient storage temperature - max

80 °C

### Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

## Electro magnetic compatibility

### Emitted interference

According to EN 60947-1

### Interference immunity

According to EN 60947-1

## Terminal capacities

### Terminal capacity (flexible with ferrule)

1 x (0.75 - 2.5) mm<sup>2</sup>, Control circuit cables

2 x (0.75 - 10) mm<sup>2</sup>, Main cables

2 x (0.75 - 2.5) mm<sup>2</sup>, Control circuit cables

1 x (0.75 - 16) mm<sup>2</sup>, Main cables

### Terminal capacity (solid)

1 x (0.75 - 16) mm<sup>2</sup>, Main cables

1 x (0.75 - 4) mm<sup>2</sup>, Control circuit cables

2 x (0.75 - 2.5) mm<sup>2</sup>, Control circuit cables

2 x (0.75 - 10) mm<sup>2</sup>, Main cables

### Terminal capacity (solid/stranded AWG)

18 - 14, Control circuit cables

Single 18 - 6, double 18 - 8, Main cables

### Terminal capacity (stranded)

1 x 16 mm<sup>2</sup>, Main cables

### Stripping length (main cable)

10 mm

### Stripping length (control circuit cable)

10 mm

### Screw size

M5, Terminal screw, Main cables

M3.5, Terminal screw, Control circuit cables

### Screwdriver size

0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver

2, Terminal screw, Pozidriv screwdriver

### Tightening torque

1.2 Nm, Screw terminals, Control circuit cables

3.2 Nm, Screw terminals, Main cables

## Electrical rating

Rated breaking capacity at 220/230 V

170 A

Rated breaking capacity at 380/400 V

170 A

Rated breaking capacity at 500 V

170 A

Rated breaking capacity at 660/690 V

120 A

Rated operational current (I<sub>e</sub>) at AC-1, 380 V, 400 V, 415 V

40 A

Rated operational current (I<sub>e</sub>) at AC-3, 220 V, 230 V, 240 V

18 A

Rated operational current (I<sub>e</sub>) at AC-3, 380 V, 400 V, 415 V

18 A

Rated operational current (I<sub>e</sub>) at AC-3, 440 V

18 A

Rated operational current (I<sub>e</sub>) at AC-3, 500 V

18 A

Rated operational current (I<sub>e</sub>) at AC-3, 660 V, 690 V

12 A

Rated operational current (I<sub>e</sub>) at AC-4, 220 V, 230 V, 240 V

10 A

Rated operational current (I<sub>e</sub>) at AC-4, 440 V

10 A

Rated operational current (I<sub>e</sub>) at AC-4, 500 V

10 A

Rated operational current (I<sub>e</sub>) at AC-4, 660 V, 690 V

8 A

Rated operational current (I<sub>e</sub>) at DC-1, 60 V

35 A

Rated operational current (I<sub>e</sub>) at DC-1, 110 V

35 A

Rated operational current (I<sub>e</sub>) at DC-1, 220 V

35 A

Rated insulation voltage (U<sub>i</sub>)

690 V

Rated making capacity up to 690 V (cos phi to IEC/EN 60947)

238 A

Rated operational power at AC-3, 240 V, 50 Hz

5.5 kW

Rated operational power at AC-3, 380/400 V, 50 Hz

7.5 kW

Rated operational power at AC-3, 415 V, 50 Hz

10 kW

Rated operational power at AC-3, 440 V, 50 Hz

10.5 kW

Rated operational power at AC-3, 500 V, 50 Hz

12 kW

Rated operational power at AC-3, 690 V, 50 Hz

11 kW

Rated operational power at AC-4, 220/230 V, 50 Hz

2.5 kW

Rated operational power at AC-4, 240 V, 50 Hz

3 kW

Rated operational power at AC-4, 415 V, 50 Hz

5 kW

Rated operational power at AC-4, 440 V, 50 Hz

5.5 kW

Rated operational power at AC-4, 500 V, 50 Hz

6 kW

Rated operational power at AC-4, 660/690 V, 50 Hz

6.5 kW

Rated operational voltage (Ue) at AC - max

690 V

## Switching capacity

Switching capacity (main contacts, general use)

40 A, Maximum motor rating (UL/CSA)

## Short-circuit rating

Short-circuit current rating (basic rating)

5 kA, SCCR (UL/CSA)

125 A, max. CB, SCCR (UL/CSA)

125 A, max. Fuse, SCCR (UL/CSA)

Short-circuit current rating (high fault at 480 V)

50/32 A, max. CB, SCCR (UL/CSA)

125/70 A, Class J, max. Fuse, SCCR (UL/CSA)

10/65 kA, CB, SCCR (UL/CSA)

10/100 kA, Fuse, SCCR (UL/CSA)

Short-circuit current rating (high fault at 600 V)

10/22 kA, CB, SCCR (UL/CSA)

10/100 kA, Fuse, SCCR (UL/CSA)

50/32 A, max. CB, SCCR (UL/CSA)

125/70 A, Class J, max. Fuse, SCCR (UL/CSA)

Short-circuit protection rating (type 1 coordination) at 400 V

63 A gG/gL

Short-circuit protection rating (type 1 coordination) at 690 V

50 A gG/gL

Short-circuit protection rating (type 2 coordination) at 400 V

35 A gG/gL

Short-circuit protection rating (type 2 coordination) at 690 V

35 A gG/gL

## Conventional thermal current I<sub>th</sub>

Conventional thermal current I<sub>th</sub> (1-pole, enclosed)

80 A

Conventional thermal current I<sub>th</sub> (3-pole, enclosed)

32 A

Conventional thermal current I<sub>th</sub> at 55°C (3-pole, open)

37 A

Conventional thermal current I<sub>th</sub> of main contacts (1-pole, open)

88 A

## Magnet system

Arcing time

10 ms

Switching capacity (auxiliary contacts, general use)

10 A, 600 V AC, (UL/CSA)

1 A, 250 V DC, (UL/CSA)

Switching capacity (auxiliary contacts, pilot duty)

P300, DC operated (UL/CSA)

A600, AC operated (UL/CSA)

Drop-out voltage

AC operated:  $0.6 - 0.3 \times U_C$ , AC operated

Duty factor

100 %

Pick-up voltage

$0.8 - 1.1 \text{ V AC} \times U_c$

Power consumption, pick-up, 50 Hz

52 VA, Dual-frequency coil in a cold state and  $1.0 \times U_s$ , at 50 Hz

Power consumption, pick-up, 60 Hz

67 VA, Dual-frequency coil in a cold state and  $1.0 \times U_s$ , at 60 Hz

Power consumption, sealing, 50 Hz

2.1 W, Dual-frequency coil in a cold state and  $1.0 \times U_s$ , at 50 Hz

7.1 VA, Dual-frequency coil in a cold state and  $1.0 \times U_s$ , at 50 Hz

Power consumption, sealing, 60 Hz

2.1 W, Dual-frequency coil in a cold state and  $1.0 \times U_s$ , at 60 Hz

8.7 VA, Dual-frequency coil in a cold state and  $1.0 \times U_s$ , at 60 Hz

Rated control supply voltage ( $U_s$ ) at AC, 50 Hz - min

230 V

Rated control supply voltage ( $U_s$ ) at AC, 50 Hz - max

230 V

Rated control supply voltage ( $U_s$ ) at AC, 60 Hz - min

240 V

Rated control supply voltage ( $U_s$ ) at AC, 60 Hz - max

240 V

Rated control supply voltage ( $U_s$ ) at DC - min

0 V

Rated control supply voltage ( $U_s$ ) at DC - max

0 V

Switching time (AC operated, make contacts, closing delay) - min

16 ms

Switching time (AC operated, make contacts, closing delay) - max

22 ms

Switching time (AC operated, make contacts, opening delay) - min

8 ms

Switching time (AC operated, make contacts, opening delay) - max

14 ms

## Motor rating

Assigned motor power at 115/120 V, 60 Hz, 1-phase  
2 HP

Assigned motor power at 200/208 V, 60 Hz, 3-phase  
5 HP

Assigned motor power at 230/240 V, 60 Hz, 1-phase  
3 HP

Assigned motor power at 230/240 V, 60 Hz, 3-phase  
5 HP

Assigned motor power at 460/480 V, 60 Hz, 3-phase  
10 HP

Assigned motor power at 575/600 V, 60 Hz, 3-phase  
15 HP

## Safety

### Safe isolation

440 V AC, Between the contacts, According to EN 61140

440 V AC, Between coil and contacts, According to EN 61140

## Communication

### Connection

Screw terminals

### Connection to SmartWire-DT

No

## Contacts

### Number of contacts (normally open contacts)

1

### Number of auxiliary contacts (normally closed contacts)

0

### Number of auxiliary contacts (normally open contacts)

1

## Special purpose ratings

### Special purpose rating of ballast electrical discharge lamps

40 A (480V 60Hz 3phase, 277V 60Hz 1phase)

40 A (600V 60Hz 3phase, 347V 60Hz 1phase)

### Special purpose rating of definite purpose rating

18 A, FLA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA)

108 A, LRA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA)

### Special purpose rating of elevator control

11 A, 200 V 60 Hz 3-ph, (UL/CSA)

9.6 A, 240 V 60 Hz 3-ph, (UL/CSA)

11 A, 600 V 60 Hz 3-ph, (UL/CSA)

10 HP, 600 V 60 Hz 3-ph, (UL/CSA)

3 HP, 200 V 60 Hz 3-ph, (UL/CSA)

11 A, 480 V 60 Hz 3-ph, (UL/CSA)

7.5 HP, 480 V 60 Hz 3-ph, (UL/CSA)

3 HP, 240 V 60 Hz 3-ph, (UL/CSA)

### Special purpose rating of refrigeration control (CSA only)

180 A, LRA 600 V 60 Hz 3phase; (CSA)

40 A, FLA 480 V 60 Hz 3phase; (CSA)

240 A, LRA 480 V 60 Hz 3phase; (CSA)

30 A, FLA 600 V 60 Hz 3phase; (CSA)

### Special purpose rating of resistance air heating

40 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA)

40 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA)

#### Special purpose rating of tungsten incandescent lamps

40 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA)

40 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA)

## Design verification

Equipment heat dissipation, current-dependent  $P_{vid}$

2.1 W

Heat dissipation capacity  $P_{diss}$

0 W

Heat dissipation per pole, current-dependent  $P_{vid}$

0.7 W

Rated operational current for specified heat dissipation ( $I_n$ )

18 A

Static heat dissipation, non-current-dependent  $P_{vs}$

2.1 W

#### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

#### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

#### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

#### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

#### 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

#### 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.2.7 Inscriptions

Meets the product standard's requirements.

#### 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.4 Clearances and creepage distances

Meets the product standard's requirements.

#### 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be

evaluated.

#### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

#### 10.8 Connections for external conductors

Is the panel builder's responsibility.

#### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

#### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

#### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

#### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

#### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Resurse

### Characteristic curve

[eaton-contactors-switch-dilm-characteristic-curve.eps](#)

[eaton-contactors-switch-dilm-characteristic-curve-002.eps](#)

### Desene

[eaton-contactors-dilm-dimensions.eps](#)

### Instrucțiuni de instalare

[IL03407014Z2021\\_09.pdf](#)

### Scheme electrice

[eaton-contactors-contact-dilm-wiring-diagram.eps](#)